


Portland cement for the export (Eagle brand) DPR of Korea

| | |
|-------------------------------------|--|
| Final Goal | Exportation of eagle brand cement |
| Author | Kohler Patrick, Business Agent and Consultant in Switzerland |
| First Date | 2009-03-15 |
| Deadline | Not specified |
| Date of Last Modifications | 2009-03-15 |
| Revision N° | 1 |
| News related to this project | None |
| Other informations | None |
| Remarks | It complies with UK standard: BSS12-1978 32.5R. |

| | |
|-----------------------------|---|
| General Informations | |
| Typical Application | <p>Portland cement is the most common type of cement in general use around the world, because it is a basic ingredient of concrete, mortar, stucco and most non-specialty grout. It is a fine powder produced by grinding Portland cement clinker (more than 90%), a limited amount of calcium sulfate which controls the set time, and up to 5% minor constituents (as allowed by various standards).</p> <p>As defined by the European Standard EN197.1, "Portland cement clinker is a hydraulic material which shall consist of at least two-thirds by mass of calcium silicates ($3\text{CaO}\cdot\text{SiO}_2$ and $2\text{CaO}\cdot\text{SiO}_2$), the remainder consisting of aluminium- and iron-containing clinker phases and other compounds. The ratio of CaO to SiO₂ shall not be less than 2.0. The magnesium content (MgO) shall not exceed 5.0% by mass."</p> |
| Photo |  |
| Appearance | Dark grey colored. |
| Packing | 50Kg Net PP bagged |
| Price | US\$37.00 per Mt |
| Importation Route | FOB Nampo, DPR Korea |
| Quantity | To negotiate |
| Conditions | Expendable after first shipment |